


US Visual Approaches: lessons from the LH458 incident

Alex Gries & Andy Spencer
22 November, 2023



On October 16, the crew of a **Lufthansa A350** inbound to San Francisco found themselves in an unenviable situation: a seemingly unnecessary **last-minute diversion** to Oakland after a long-haul flight. The diversion was forced by ATC, following the crews inability to accept a visual approach. The incident highlights issues with visual approaches in the US, particularly during late-night arrivals.

LH458 - What happened?

Here's how it went down:

ATC: *Expect a visual approach.*

CREW: *We can't do visual approaches at night-time due to company procedures.*

ATC: *In that case, expect delays.*

At this point in the story, instead of a visual approach on runway 28R, the crew were told to expect an **ILS approach on runway 28L**. They were then put into a hold - perfectly understandable for their integration into the approach sequence. After holding for 20 minutes, ATC advised there would be another 10-minute delay. 10 minutes go by.

4 minutes later:

CREW: *If we can't land soon, we'll have to declare a fuel emergency.*

ATC: *What's your diversion airport?*

CREW: *Oakland.*

ATC: *You need vectors to Oakland?*

CREW: *Er, no. What's the problem here?*


ATC: *I can't have this conversation with you. Either divert to Oakland, or you can continue to hold, it's up to you.*

CREW: *Okay, you promised me 10 minutes, that ran out four minutes ago. So how many more minutes?*


ATC: Conversation is over. You want to divert? Or you want to continue with the delay?

CREW: We're diverting to Oakland.

This resulted in a **flight time of over 12 hours**, landing in Oakland an hour after commencing the approach to KSFO (and at 7 am Munich local time - the crew's local time). After **one hour of turnaround**, the crew resumed their flight to KSFO, which took **another 45-minutes** block to block.



The first flight: Munich - San Francisco (diverted to Oakland)



The second flight: Oakland - San Francisco

The delays are crucial to this story. It's not uncommon for delays to occur, but ATC announcing a 10-minute delay (which is essentially treated as an EAT or *Expected Approach Time*), and then not adhering to it (especially after 30 minutes of holding) is not great. This significantly alters the situation and could have had more severe consequences.

A video of the flight path, including part of the audio between the crew and ATC is here:

What's the problem?

In terms of flight safety, one can question the wisdom of subjecting the crew to **significant extra fatigue after a long flight**. Was it really not possible to create an additional two or three nautical miles of spacing between two aircraft for over 30 minutes to accommodate this flight?

Long Haul operations entail heightened risks due to extended duties and activities during circadian lows. While instrumental in facilitating aviation, the prevailing attitude within the US ATC tends to **prioritize maximizing movements** without seemingly adequate consideration for the nature of specific operations. It's essential to **recognize that not all arrivals are equal**; when a pilot communicates inability, it's not mere difficulty but a conscientious acknowledgment of the immense responsibility for the safety of hundreds on their shoulders. After a lengthy night of flying, we would all find it challenging to justify opting for a visual approach as the safer choice.

The FAA prohibits visual separation on an ILS. Consequently, questions arise about the request made to the crew in this regard, as well as **the system that forces night-time visual approaches on all aircraft**, regardless of the fatigue level of the crews and their unique circumstances.

This is a systemic issue. But it does feel like there is room to hope for a more comprehensive systemic approach to avoid putting a crew in a potentially safety-compromising situation.

Why was there a delay in the flight's approach?

While a delay in air traffic is understandable, adhering to the announced duration (which clearly had the characteristics of an *Expected Approach Time*) is crucial to ensure safety. In this case, the crew experienced confusion when their EAT was not met, leading to **concerns about fuel reserves and potential emergencies**. Efficient coordination between ATC and crews is essential to prevent such situations.

Could the flight have been accommodated within the initially announced timeframe?

Considering that the flight had already spent over 30 minutes holding, it seems reasonable to think that they could have been inserted and provided with a few nautical miles in a thirty-minute sequence.

Based on the announcement of an additional 10-minute holding, this crew could have converted their diversion reserves into holding time, as allowed by regulations, and found themselves **unable to divert and potentially facing a fuel emergency**. This would have disrupted the sequence far more than adjusting a few nautical miles over 30 minutes.

Some aircraft, like the 777, may have to **land with reduced flap settings in case of low fuel quantity**, further diminishing margins. This outcome does not align with improved safety, and ATC should consider this for these long-haul approach flights.

It should be remembered that the pilots of this flight did all they could to communicate in a clear manner (*sans* the frustration at the end of the conversation) that they were unable to do what was initially conveyed. The fact that they were **forced into a corner of a very near fuel emergency by the actions of ATC** should highlight just how critical it is for us to **get this fixed, pronto**.

What can be done to improve safety and coordination in such cases?

Air traffic management needs to communicate effectively with flight crews, announce and adhere to EAT's, and consider unique circumstances, especially for long-haul flights at night.

The FAA's Safety Alert for Operators (SAFO) 21005 states that 'it is the pilot's responsibility, according to 14 C.F.R. § 91.3, to advise ATC as soon as possible if a visual approach is not desired.' This SAFO recommends 'Communicating "UNABLE" to ATC when, in the judgment of the pilot-in-command, compliance with a specific instruction, request, or clearance may reduce safety.'

Ultimately, a crew adhering to the FAA's SAFO should not find themselves in a situation that compromises the safety of their flight by subjecting them to additional fatigue. The situation is even more concerning given the example of this flight and its implications for the crew, substantial financial consequences for the airline, and potentially for some passengers. This may make **future crews hesitant about declining a visual approach**, even when safety would necessitate it, as emphasized by the SAFO.

Why are visual approaches important?

Visual approaches allow for increased airport efficiency when weather conditions permit.

At KSFO/San Francisco, efforts were made in 2016 to enhance airport efficiency through new approach procedures, such as the RNP to GLS study. Being the seventh busiest airport in the US at the time, the airport could, during good weather conditions, sequence arrivals to runways 28L and 28R using visual separation, resulting in a peak arrival rate of 56 per hour. However, less favourable weather conditions necessitated instrument approach procedures, reducing airport efficiency to 28 to 36 arrivals per hour.

This highlights the critical role of visual separation in maximizing KSFO's capacity, despite runways being only 750 feet apart.

However, we must remember that **separations primary objective is safety**, as evidenced by recent updates in the FAA's Order on Simultaneous Dependent Approaches to Closely Spaced Parallel Runways, which consider Consolidated Wake Turbulence (CWT) procedures.

The visual approaches involve reducing the spacing between arriving aircraft, which can lead to higher traffic capacity and profitability. But they also **shift some responsibility to the flight crew**, particularly the captain, who must accept the risk of wake turbulence and become responsible for maintaining proper spacing to benefit the system.

This dual nature of visual approaches underscores the delicate balance between efficiency and safety in aviation operations.

How does the US differ from international standards regarding visual approaches?

The US aviation regulations **do not strictly adhere to the ICAO standards** regarding visual approaches. In the US, air traffic controllers may initiate a visual approach **without the explicit consent of the pilot**, unlike standard ICAO procedures, which require pilot agreement. This difference in approach procedures can lead to unique challenges. For more info, have a read of this IFALPA Bulletin.

Key Issues

This recent incident in San Francisco highlights several issues:

1. **Crew's Spacing Responsibility:** Visual approaches in airports enhance efficiency but shift responsibility to flight crew for maintaining spacing and managing risks.
2. **US vs ICAO Practices:** There is a discrepancy between US aviation practices and ICAO standards.
3. **ATC-Crew Safety Coordination:** The incident shows the need for precise coordination between air traffic management and flight crews to ensure the safety of operations.
4. **Night Approach Restrictions:** Certain airlines have procedures that prohibit crews from conducting night visual approaches, and ATC needs to be aware of and accommodate these restrictions.
5. **Managing Approach Delays:** The delay in the flight's approach raises questions about managing holding times and adhering to announced durations.
6. **Risks in Night Approaches:** Long-haul flights arriving at night using visual approaches might pose safety risks, considering crew fatigue and FAA's SAFO.
7. **Safeguarding Flight Operations:** A comprehensive systemic approach is required to prevent compromising situations for flight crews, emphasizing effective communication, adherence to EAT's, and crew judgment.
8. **ATC Safety Guidelines:** ATCs must be aware of safety guidelines (SAFOs) to ensure crew adherence and avoid jeopardizing safety.
9. **Crew Safety Priority:** Prioritizing safety over convenience is essential for flight crews.

This final point – ensuring flight crews are not hesitant to prioritize safety over convenience – is vital to maintaining the highest level of aviation safety. The KSFO incident serves as a reminder that **aviation is a delicate balance of safety, efficiency, and coordination.**